

Hydrostatic duplex rollers

webermt

The Colours of Progress

DVH

DVH 550



The exemplary design of the DVH hydrostatic duplex rollers has now been successfully adapted to a smaller format.

The DVH 550 L and R are the ideal solution for asphalt repair jobs.

- Front-mounted engine for easy maintenance.
- Large-volume water tank.
- Guide bar with infinitely variable speed adjustment and dead man's control.
- Vibration can be switched on and off via hand lever at any engine speed.
- No vibration transmission to the handle thanks to isolated engine assembly.
- Central lifting device for easy, safe transport.
- Mechanical parking brake to prevent unintended movements.

The DVH 550 and its technical data:

Typ		DVH 550 L	DVH 550 R
machine weight	kg (lbs)	345 (760)	330 (728)
operating weight	kg (lbs)	365 (805)	350 (772)
drum width	cm (in.)	55 (22)	55 (22)
drum diameter	cm (in.)	32.5 (13)	32.5 (13)
centrifugal force	kN (lbs)	8 (1800)	8 (1800)
frequency	Hz (rpm)	60 (3600)	60 (3600)
engine make		Lombardini	Robin
engine type		Diesel 15 LD 315	4-stroke gasoline EH 25
max. output, DIN 70020	kW/HP	5/6.8	6.3/8.5

We reserve the right to alter these specifications.

