

PRODUCT SPECIFICATIONS FOR 326

ENGINE

| | |
|-----------------------------|--------|
| Net Power - ISO 9249 | 201 HP |
|-----------------------------|--------|

| | |
|---------------------|----------|
| Engine Model | Cat C7.1 |
|---------------------|----------|

| | |
|---------------------------------|--------|
| Engine Power - ISO 14396 | 202 HP |
|---------------------------------|--------|

| | |
|-------------|------|
| Bore | 4 in |
|-------------|------|

| | |
|---------------|------|
| Stroke | 5 in |
|---------------|------|

| | |
|---------------------|---------------------|
| Displacement | 428 in ³ |
|---------------------|---------------------|

HYDRAULIC SYSTEM

| | |
|-----------------------------------|-------------------------|
| Main System - Maximum Flow | 515 l/min (136 gal/min) |
|-----------------------------------|-------------------------|

| | |
|-------------------------------------|----------|
| Maximum Pressure - Equipment | 5075 psi |
|-------------------------------------|----------|

| | |
|---|----------|
| Maximum Pressure - Equipment - Lift Mode | 5510 psi |
|---|----------|

| | |
|----------------------------------|----------|
| Maximum Pressure - Travel | 5075 psi |
|----------------------------------|----------|

| | |
|---------------------------------|----------|
| Maximum Pressure - Swing | 4118 psi |
|---------------------------------|----------|

SWING MECHANISM

| | |
|--------------------|------------|
| Swing Speed | 10.5 r/min |
|--------------------|------------|

| | |
|-----------------------------|--------------|
| Maximum Swing Torque | 78182 ft·lbf |
|-----------------------------|--------------|

WEIGHTS

| | |
|-------------------------|----------|
| Operating Weight | 57100 lb |
|-------------------------|----------|

SERVICE REFILL CAPACITIES

| | |
|--|----------------|
| Fuel Tank Capacity | 125.2 gal (US) |
| Cooling System | 6.6 gal (US) |
| Engine Oil | 6.6 gal (US) |
| Swing Drive | 2.6 gal (US) |
| Final Drive - Each | 1.5 gal (US) |
| Hydraulic System - Including Tank | 81.9 gal (US) |
| Hydraulic Tank | 38.8 gal (US) |
| DEF Tank | 10.8 gal (US) |

DIMENSIONS

| | |
|-------------------------------------|--|
| Boom | Reach 5.9 m (19'4") |
| Stick | Reach 2.95 m (9'8") |
| Bucket | HD 1.54 m ³ (2.01 yd ³) |
| Shipping Height - Top of Cab | 9.84 ft |
| Handrail Height | 9.84 ft |
| Shipping Length | 33 ft |
| Tail Swing Radius | 9.84 ft |
| Counterweight Clearance | 1.44 ft |
| Ground Clearance | 3.48 ft |
| Track Length | 15.3 ft |
| Length to Center of Rollers | 12.5 ft |
| Track Gauge | 8.5 ft |
| Transport Width | 10.5 ft |

WORKING RANGES & FORCES

| | |
|--|--|
| Maximum Digging Depth | 22.38 ft |
| Boom | Reach 5.9 m (19'4") |
| Stick | Reach 2.95 m (9'8") |
| Bucket | HD 1.54 m ³ (2.01 yd ³) |
| Maximum Reach at Ground Level | 33.2 ft |
| Maximum Cutting Height | 31.63 ft |
| Maximum Loading Height | 21.72 ft |
| Minimum Loading Height | 7.84 ft |
| Maximum Depth Cut for 2440 mm (8 ft) Level Bottom | 21.78 ft |
| Maximum Vertical Wall Digging Depth | 16.77 ft |
| Bucket Digging Force - ISO | 37318 lbf |
| Stick Digging Force - ISO | 27202 lbf |

326 STANDARD EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

CAB

High-resolution 203 mm (8 in) LCD touchscreen monitor

CAT TECHNOLOGIES

Cat Product Link™

Cat GRADE with 2D (Optional with a Super Long Reach boom)

Cat GRADE with Assist (Optional with a Super Long Reach boom)

Cat PAYLOAD (Optional with a Super Long Reach boom)

2D E-Fence (Optional with a Super Long Reach boom)

Lift Assist (Optional with a Super Long Reach boom)

Auto Dig Boost

ENGINE

- Three selectable power modes
- One-touch low idle with auto engine speed control
- Auto engine idle shutdown
- 52° C (125° F) high-ambient cooling capacity with de-rate
- 18° C (0° F) cold start capability
- Double element air filter with integrated precleaner
- Reversing electric cooling fans
- Biodiesel capability up to B20

HYDRAULIC SYSTEM

- Boom and stick regeneration circuits
- Auto hydraulic warm up
- Auto two-speed travel
- Boom and stick drift reduction valve

UNDERCARRIAGE AND STRUCTURES

- Tie-down points on base frame
- 4600 kg (10,141 lb) counterweight

ELECTRICAL SYSTEM

- Two 1,000 CCA maintenance free batteries
- Programmable time-delay LED working lights
- LED chassis light, left-hand/right-hand boom lights, cab lights

SERVICE AND MAINTENANCE

- Sampling ports for Scheduled Oil Sampling (S·O·S)
- Ground-level and platform-level engine oil dipsticks

SAFETY AND SECURITY

- Rearview camera
- Right-side-view camera
- Ground-level engine shutoff switch

Right-hand handrail and hand hold

Signaling/warning horn

326 OPTIONAL EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

CAB

ROPS, Comfort cab with mechanical seat suspension

ROPS, standard sound suppression, air-adjustable seat with heat (Deluxe only)

ROPS, advanced sound suppression, auto-adjustable seat with heat and air ventilation (Premium only)

High-resolution 254 mm (10 in) LCD touchscreen monitor

CAT TECHNOLOGIES

Cat GRADE with Advanced 2D (Optional with a Super Long Reach boom)

Cat GRADE with 3D (Optional with a Super Long Reach boom)

ENGINE

-32° C (-25° F) cold start capability

HYDRAULIC SYSTEM

Boom and stick lowering check valves

Hammer return filter circuit

Combined Tool Control (two pump, one/two way high-pressure flow)

Medium-pressure circuit

Quick coupler circuit

BOOMS AND STICKS

5.9 m (19'4") HD reach boom, 2.95 m (9'8") HD reach stick, long undercarriage (Europe and Japan only - long narrow undercarriage also available in Europe only)

5.9 m (19'4") reach boom, 3.6 m (11'10") reach stick, long undercarriage (North America only)

5.9 m (19'4") reach boom, 2.95 m (9'8") reach stick, long undercarriage (Long narrow undercarriage also available in Europe only)

5.9 m (19'4") reach boom, 2.5 m (8'2") reach stick, long undercarriage (Long narrow undercarriage also available in Europe only)

2.8 m + 3.3 m (9'2" + 10'10") VA boom, 2.95 m (9'8") reach stick, long undercarriage (Europe only.) (Long narrow undercarriage also available in Europe only)

2.8 m + 3.3 m (9'2" + 10'10") VA boom, 2.5 m (8'2") reach stick, long undercarriage (Europe only.) (Long narrow undercarriage also available in Europe only)

10.2 m (33'6") SLR boom, 7.85 m (25'9") SLR stick, long undercarriage (Long narrow undercarriage also available in Europe only)

UNDERCARRIAGE AND STRUCTURES

600 mm (24") triple grouser shoes

700 mm (28") triple grouser shoes

790 mm (31") triple grouser shoes

900 mm (35") triple grouser shoes

6700 kg (14,771 lb) counterweight

ELECTRICAL SYSTEM

360° lighting

Premium surround lighting package

SERVICE AND MAINTENANCE

Electric refueling pump with auto shut off

SAFETY AND SECURITY

360° visibility (Requires 254 mm [10 in] monitor)